

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date:12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

SECTION 1: Name of the substance or mixture and the undertaking

1.1 Product identifier

Item No. (Manufacturer/Supplier): 1180
Trade name/name Scheidel Asur Allround Abbeizer

1.2 Relevant identified uses of the substance or mixture and uses, that are not recommended

Relevant identified uses

For removing KH paints,oil paints, thick-layeralac, building paints.

1.3 Details of the supplier providing the safety data sheet

Supplier (Manufacturer/Importer/Downstream User/Distributor)

Scheidel GmbH & Co. KG Phone: + 49 (0)9543 8426 0
Jahnstraße 38-42 Fax: + 49 (0)9543 8426 31
D-96114 Hirschaid
Germany
Laboratory - Application Technology + 49 (0)9543 8426 19
E-mail(expert) sicherheit@scheidel.com

1.3.1 Details of the Irish supplier providing the safety data sheet

Irish Supplier (Manufacturer/Importer/Downstream User/Distributor)

Conservation Technology Ltd. Phone: 01 455 9511
Davitt Road E-mail: info@conservationtech.ie
Dublin 12
D12 YXK8
Ireland

1.4 Emergency number

Emergency number Phone-tags: + 49 (0)9543 8426 19
Telephone-night: + 49 (0)9543 8426 18

SECTION 2: Possible dangers

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous within the meaning of Regulation (EC) No 1272/2008 [CLP].

Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Skin Irrit. 2 / H315	Etching- /irritant effect on the skin	Causes skin irritation.
Eye Irrit. 2 / H319	Severe eye damage/irritation	Causes severe eye irritation.

2.2 Label elements

The product is classified and labelled according to ECdirectives or the respective national laws.

Labelling in accordance with Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms



Attention

Hazard warnings

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date: 12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

H302 Harmful to health in case of concealment.

H315 Causes skin irritation.

H319 Causes severe eye irritation.

Safety

P264 After use, wash hands thoroughly.

P270 Do not eat, drink or smoke when used.

P280 Protective gloves/Protective clothing/Eye protection/Wear face protection.

P301 + P312 AT CLOSED: Call GIFT INFORMATION CENTRE or doctor in case of discomfort.

P302 + P352 AT CONTACT WITH THE HAUT: Wash with lots of water and soap.

P305 + P351 + P338 AT CONTACT WITH THE EYES: Rinse gently with water for a few minutes. Remove any existing contact lenses if possible. Continue to rinse.

P332 + P313 In case of skin irritation: Seek medical advice / seek medical attention.

P337 + P313 In case of persistent eye irritation: Seek medical advice / seek medical attention.

P362 + P364 Remove contaminated clothing and wash before re-wearing it.

P501 Contents/containers of industrial incineration plant.

P101 If medical advice is required, keep packaging or label.

P102 Must not end up in the hands of children.

Dangerous components for labelling

N-n-Butylpyrrolidon

Supplementary hazard characteristics (EU)

not applicable

2.3 Other hazards

No information is available.

SECTION 3: Composition / Information on ingredients

3.2 Mixtures

description Solvent mixture, highly viscous

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EG-Nr.	REACH no.	Wt%
CAS-Nr.	description	
INDEX-Nr.	Classification: // Note	
222-437-8	01-2120062728-48-0000	10 < 25
3470-98-2	N-n-Butylpyrrolidon Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319	
200-579-1	01-2119491174-37-0000	
64-18-6	Formic acid	< 2,5
607-001-00-0	Flam. Liq. 3 H226 / Acute Tox. 4 H302 / Acute Tox. 3 H331 / Skin Corr. 1A H314 Specific concentration limit (SCL): Skin Corr. 1A H314 >= 90 / Skin Corr. 1B H314 >= 10 / Skin Irrit. 2 H315 >= 2 / Eye Irrit. 2 H319 >= 2	

Additional information

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date: 12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

Full text of the classifications: see section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General Notes

In the event of symptoms or in cases of doubt, seek medical advice. In case of unconsciousness do not administer anything through the mouth, put in stable side position and seek medical advice.

If inhaled

Bring those affected to the fresh air and keep warm and calm. In case of irregular breathing or respiratory arrest, initiate artificial ventilation.

After skin contact

Dirty, soaked clothes take off immediately. When in contact with the skin, wash immediately with plenty of water and soap. Do not use solvents or dilutions.

After eye contact

Rinse gently with water for a few minutes. Remove any existing contact lenses if possible. Continue to rinse. Immediately seek medical advice.

After ingestion

When swallowed mouth rinse with water (only if accident is in consciousness). Immediately seek medical advice. Keep those affected quiet. NO vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Seek medical advice in the event of symptoms or in cases of doubt.

4.3 References to emergency medical assistance or special treatment

Elementary assistance, decontamination, symptomatic treatment.

SECTION 5: Fire-fighting measures

5.1 Extinguishing agents

Suitable extinguishing agents

alcohol-resistant foam, carbon dioxide, powder, spray mist, (water)

5.2 Specific hazards posed by the substance or mixture

In the event of a fire, thick black smoke is produced. Inhalation of dangerous decomposition products can cause serious damage to health.

5.3 Provide instructions for firefighting breathing apparatus.

Unsuitable extinguishing agents of sharp water jet

Additional notes

Closed containers near the fire scene with water cool. Do not allow extinguishing water to enter sewers, soil, or water bodies.

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date: 12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

SECTION 6: Measures in the event of accidental release

6.1 Imitate personal precautions, air protective equipment and procedures to be used in emergencies

Aeration the area concerned. Do not inhale vapours

6.2 Environmental protection measures

Do not allow to enter the sewers or waters. In the event of pollution of rivers, lakes or waste pipes, in accordance with local laws, inform the relevant competent authorities.

6.3 Methods and materials for retention and cleaning

Leaked material with incombustible absorber (e.B. limit sand, soil, vermiculite, silica and collect for disposal in the containers provided for this purpose in accordance with local regulations (see section 13). Post-cleaning with detergents, do not use solvents

6.4 Reference to other sections

(see sections 7 and 8).

SECTION 7: Handling and storage

7.1 Safe handling measures

Notes on safe handling

Avoid contact with skin, eyes and clothing. Avoid inhalation of abrasive dusts. Do not eat, drink, smoke at work.

Personal protective equipment: see section 8. Never empty containers with pressure - no pressure vessel! Always store in containers that correspond to the same material of the original owner. Comply with legal protection and safety regulations.

7.2 Conditions for safe storage taking into account intolerances

Requirements for storage rooms and containers

Storage in accordance with the Operational Security Ordinance. Keep containers tightly closed. Never empty containers with pressure - no pressure vessel! Smoking prohibited. Unauthorized persons are prohibited from entering. Store the container carefully closed upright to prevent any leakage. Soils must comply with the "Guidelines for the Prevention of Ignition Hazards due to Electrostatic Charges (TRBS 2153)".

Advice on common storage

Keep away from highly acidic and alkaline materials as well as oxidizing agents.

Further information on storage conditions

Observe the notes on the label. Store in well-ventilated and dry rooms between 10 °C and 35 °C. Protect from heat and direct sunlight. Keep containers tightly closed. Remove all ignition sources. Smoking prohibited. Unauthorized persons are prohibited from entering. Store containers carefully closed upright to prevent any leakage.

Storage class

(VCI-concept for the accumulation of chemicals): 10 Flammable liquids not to be assigned to any of the above storage classes

7.3 Specific End Applications

Observe the technical leaflet. Observe instructions for use.

Solutions Solutions

Giscode M-AB10 Abbeizer, solvent-containing, dichloromethane-free

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date: 12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

SECTION 8: Limitation and monitoring of exposure/personal protective equipment

8.1 Parameters to be monitored Workplace limits

Formic acid

INDEX No. 607-001-00-0 / EC No. 200-579-1 / CASNo. 64-18-6

TRGS 900, AGW, Langzeitwert: 9,5 mg/m³; 5 ppm

TRGS 900, AGW, Kurzzeitwert: 19 mg/m³; 10 ppm

Additional notes

Long-term value : Long-term workplace limit value

Short-term value : Short-term workplace limit Peak limit : Peak limit

DNEL:

Formic acid

INDEX No. 607-001-00-0 / EC No. 200-579-1 / CAS No. 64-18-6

DNEL acute inhalation (local), worker: 19 mg/m³

DNEL acute inhalation (systemic), workers: 19 mg/m³

DNEL Long-term inhalation (local), worker: 9.5 mg/m³

DNEL Long-term inhalation (systemic), Worker: 9.5 mg/m³

DNEL acute inhalation (local), consumer: 9.5 mg/m³

DNEL acute inhalation (systemic), Consumer: 9.5 mg/m³

DNEL Langzeit inhalation (local), Consumer: 3 mg/m³

DNEL Long-term inhalation (systemic), Consumer: 3 mg/m³

N-n-Butylpyrrolidon

EC No. 222-437-8 / CAS No. 3470-98-2

DNEL Long-term dermal (systemic), Worker: 10 mg/kg

DNEL Long-term inhalation (systemic), Worker: 24.1 mg/m³

DNEL Long-term oral (repeated), Consumer: 2.5 mg/kg

DNEL Long-term dermal (systemic), Worker: 10 mg/kg

DNEL Long-term inhalation (systemic), Worker: 24.1 mg/m³

DNEL Long-term oral (repeated), Consumer: 2.5 mg/kg

DNEL Long-term dermal (systemic), Consumer: 5 mg/kg

DNEL Long-term inhalation (systemic), Consumer: 17.5 mg/m³

PNEC:

Formic acid

INDEX No. 607-001-00-0 / EC No. 200-579-1 / CAS No. 64-18-6

PNEC Water, Freshwater: 2 mg/l

PNEC waters, seawater: 0.2 mg/l

PNEC waters, periodic release: 1 mg/l

PNEC Sediment, Süßwasser: 13,4 mg/kg

PNEC sediment, seawater: 1.34 mg/kg

PNEC, Boden: 1,5 mg/kg

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date:12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

PNEC Kläranlage (STP): 7,2 mg/l
N-n-Butylpyrrolidon
EC No. 222-437-8 / CAS No. 3470-98-2
PNEC Waters, Freshwater:4mg/l
PNEC waters, seawater:0.4 mg/l
PNEC waters, periodic release:1 mg/l
PNEC sediment, freshwater:29.6 mg/kg
PNEC sediment, seawater:2.96 mg/kg
PNEC, Boden: 3,57 mg/kg
PNEC Kläranlage (STP): 30,62 mg/l

8.2 Limitation and monitoring of exposure

Ensure good ventilation. This can be achieved by local or room extraction. If this is not sufficient to keep the aerosol and solvent vapor concentration below the occupational exposure limits, a suitable breathing apparatus must be worn.

Personal protective equipment

Respiratory

Where the solvent concentration exceeds the occupational exposure limits, an approved breathing apparatus suitable for that purpose shall be worn. The time limits according to GefStoffV in conjunction with the rules for the use of respiratory protection devices (BGR 190) must be observed. Only use breathing apparatus with CE number including four-digit test number.

Guard

For prolonged or repeated handling, use the glove material:KCL But object thickness of the glove material > 0.4 mm ; Penetration time (maximum wearing time)>480 min.

The instructions and information of the protective glove manufacturer regarding use, storage, maintenance and replacement must be observed. Penetration time of the glove material depending on the strength and duration of skin exposure. Recommended glove brands EN ISO 374

Protective creams can help to protect exposed areas of the skin. After a contact, these should not be applied under any circumstances.

Eyes-/Face Protection

Wear tightly closing goggles in case of risk of spraying.

Body protection

Wear antistatic clothing made of natural fibre (cotton) or heat-resistant synthetic fibre.

Protective measures

After contact, thoroughly clean skin surfaces with water and soap or use suitable cleanser.

Limitation and monitoring of environmental exposure

Do not allow to enter the sewers or waters. See section 7. No further measures are required.

SECTION 9: Physical and chemical properties

8.1 Information on the basic physical and chemical properties

Appearance:

State of aggregation: liquid

Appearance: Paste

Colour: Beige

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180
Printing date: 12.09.2019
Version: 4.0

Scheidel Asur Allround Stripper
Processing date: 12.09.2019
Issue: 09.09.2019

DE

Smell:	typical of the species
Odor threshold:	not determined
pH at 20 °C:	3 - 4 / 1.0 wt-% Method: pH electrode
Melting point/freezing point:	not determined
Start of the sied and the sieing area:	not applicable
Flashpoint:	100 °C Method: Pensky-Martens
Evaporation rate:	not determined
Flammability:	not determined
Burning time (s):	
Upper/lower flammability or explosion limits:	
Lower explosion limit:	0.95 Vol-% Method: calculated
Upper explosion limit:	47.6 vol-% Method: calculated
Steam pressure at 20 °C:	42 mbar Method: Literary value
Steam density:	not determined
Relative density:	
Density at 20 °C:	1.09 g/cm³ Method: Pycnometer
Relative density at 20 °C::	not determined
Solubility(en):	
Water solubility (g/L) at 20 °C:	partially soluble
Distribution coefficient n-octanol/water:	see section 12
Auto-ignition temperature:	> 350 °C Method: Literary value
Decomposition temperature:	not determined
Viscosity at °C:	10000 mPas
Explosive properties:	not applicable
Fire-promoting properties:	not applicable
9.2 Other information	
Solid content (%):	10.00 W-% / 0.00 L/kg / 0.00 Vol-% Remarks: Solids content (%)Remark
Solvent:	
Organic solvents:	90.0 Wt-%
aromatic hydrocarbons:	0.0 Wt-%
water:	0.0 Wt-%

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date:12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

SECTION 10: Stability and reactivity

10.1 Reactivity

No information is available.

10.2 Chemical stability

Stable when applying the recommended storage and handling requirements. For more information on proper storage: see section 7.

10.3 Possibility of dangerous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to be avoided

Stable when applying the recommended storage and handling requirements. For more information on proper storage: see section 7. Dangerous decomposition products can occur at high temperatures.

10.5 Incompatible materials

not applicable

10.6 Dangerous Decomposition Products

Dangerous decomposition product can occur at high temperatures, e..B. : Carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological data

Classification in accordance with Regulation (EC) No 1272/2008 [CLP] There is no data on the preparation itself.

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Formic acid

oral, LD50, rat:730 mg/kg Method: OECD401

inhalation (vapours), LC50, rat:7.85 mg/l (4 h)

Method:BASF Test

N-n-Butylpyrrolidone

oral, LD50, Rat 300 - 2000 mg/kg

dermal, LD50, Rabbit:> 2000 mg/kg

Etching-/irritant effect on the skin; Severe eye damage/irritation

Causes skin irritation.

Causes severe eye irritation.

Formic acid

High

Causes severe burns to the skin and severe eye damage.

N-n-Butylpyrrolidon

High

Causes skin irritation.

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date:12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

Eyes

Respiratory sensitization/skin

On the basis of the available data, the classification criteria are not met.

CMR effects (carcinogenic, mutagenic and reproductive-related effects)

On the basis of the available data, the classification criteria are not met.

Specific target organ toxicity at one-time exposure; Specific target organ toxicity in repeated exhibition

On the basis of the available data, the classification criteria are not met.

Aspiration hazard

Based on the available data, the classification criteria are not met.

Experience from practice/in humans

Prolonged and repeated contact with the product leads to skin fat loss and may cause non-allergic contact skin damage (contact dermatitis)and/or pollutant resorption. Splashes can cause irritation to the eye and reversible damage.

This product does not contain chlorinated or aromatic hydrocarbons. Nevertheless, the usual precautions must be taken when handling organic solvents.

attention!

Excessive influence, e.B. in case of poor ventilation in doors, can cause fuzzy vision. This is Fresh air supply reversible.

Summary evaluation of CMR properties

The ingredients of this mixture do not meet the requirements for CMR categories 1A or 1B according to CLP.

Remark

There is no information on the preparation itself.

SECTION 12: Environmental claims

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information on the preparation itself. Do not allow to enter the sewers or waters.

This product is degradable in wastewater treatment plants with biological purification stage. Knowledge about biodegradability is available and can be requested from us.

12.1 Toxicity

Formic acid

Fischtoxizität, LC50, Brachydanio rerio (Zebrafisch): 130 mg/l (96 h)

Methode: OECD 203

Daphniantoxizität, EC50, Daphnia magna (Large water flea):365 mg/l (48 h)

Methode: OECD 202

Algentoxizität, ErC50, Scenedesmus subspicatus: 1240 mg/l (72 h) Methode: OECD 201

N-n-Butylpyrrolidon

Fischtoxizität, LC50, Oncorhynchus mykiss (Regenbogenforelle): > 100 mg/l (96 h)

Daphnia toxicity, EC50, Daphnia magna (Large water flea):> 100 mg/l (48 h)

Algentoxizität, ErC50, Pseudokirchneriella subcapitata: > 160 mg/l

Long-term ecotoxicity

Formic acid

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date:12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

Daphnia toxicity, NOEC, Daphnia magna (Large water flea):> 102 mg/l (21 d) Method:OECD 211

12.2 Persistence and degradability

Formic acid

Degradability: 100% (9 d)

Easily biodegradable (according to OECD criteria)

12.3 Bioaccumulative potential

Formic acid

Distribution coefficient n-octanol/water: -1.9

N-n-Butylpyrrolidon

Distribution coefficient n-octanol/water: 1,265

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4 Mobility in the ground

Toxicological data are not available.

12.5 Results of the PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria set out in REACH, Annex XIII.

12.6 Other harmful effects

No information is available.

SECTION 13: Disposal Notes

13.1 Waste treatment procedures

Proper disposal / Product

Recommendation

Do not allow to enter the sewers or waters. Waste and containers must be disposed of in a secure manner. Disposal in accordance with Directive 2008/98/EC on waste and hazardous waste.

Stripper wastewater:

Always collect waste water and separate the solids via filters, gravel bed, sand trap etc. run. Caution with Channel separation systems! Obtain information from the competent authority. After consultation with the local authority, the Waste water in the rule can be discharged into the sewer system.

Paint sludge:

The separated paint sludge is house or hazardous waste (heavy metals?).

Proposal list for waste keys/waste designations according to AVV:

200129*Cleaning agents containing hazardous substances

*Hazardous waste in accordance with Directive 2008/98/EC (Waste Framework Directive).

Proper disposal / packaging recommendation

Untamminated and empty packaging may be recycled. Containers that are not properly emptied are special waste.

SECTION 14: Transport information

This mixture is not classified as hazardous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date:12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

No dangerous goods within the meaning of the transport regulations.

14.1 **UN-Number** not applicable

14.2 **Proper Un shipping designation** not applicable

14.3 **Transport hazard classes** not applicable

14.4 **Packing group** not applicable

14.5 **Environmental hazards**

Land transport (ADR/RID) not applicable

Marine pollutant not applicable

14.6 **Special precautions for the user**

Transport always in closed, upright and safe containers. Make sure that people who transport the product, know what to do in case of a leak or leak.

Notes on safe handling: see sections 6 - 8

For more information

Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG)

14.7 **EmS-No.** not applicable

Bulk transport in accordance with Annex II to the MARPOL-Convention and in accordance with the IBC Code
not applicable

SECTION 15: Legislation

15.1 **Safety, health and environmental legislation/specific legislation on the substance or mixture EU rules**
Directive 2010/75/EU on industrial emissions

VOC value (in g/L): 286.6

National rules

Notes on employment restrictions

Employment restrictions under the Maternity Regulations (92/85/EEC) for expectant or nursing mothers.

Employment restrictions under the Youth Employment Protection Act (94/33/EC).

Water hazard class (WGK)

1 weak water-hazardous

Occupational Safety Ordinance (BetrSichV)

not applicable

Technical instructions Air (TA-Luft)

TA-Luft (2002) Chapter 5.2.5 Organic Substances Class I

In total, the following values may be

mass flow: 0.10 kg/h

oder

Mass concentration: 20 mg/m³

not be exceeded

Other regulations, restrictions and prohibition regulations

Professional Association Rules (BGR)

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date:12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

Switzerland Share-VOC, SR 814,018 (Gew-%) :1,8

15.2 Chemical safety assessment

A chemical safety assessment has been carried out for the following substances in this mixture:

EG-Nr. CAS-Nr.	Description	REACH-Nr.
222-437-8 3470-98-2	N-n-Butylpyrrolidon	01-2120062728-48-0000
200-579-1 64-18-6	Ameisensäure	01-2119491174-37-0000

SECTION 16: Other information

Full text of the classification in Section 3:

Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Skin Irrit. 2 / H315	Etching- /irritant effect on the skin	Causes skin irritation.
Eye Irrit. 2 / H319	Severe eye damage/irritation	Causes severe eye irritation.
Flam. Liq. 3 / H226	Flammable liquids	Liquid and steam flammable.
Acute Tox. 3 / H331	Acute toxicity (inhalation)	Toxic when inhaled.
Skin Corr. 1A / H314	Etching- /irritant effect on the skin	Causes severe burns to the skin and severe eye damage.

Classification procedure

Classification of mixtures and evaluation method used in accordance with Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4	Acute toxicity (oral)	calculation method.
Skin Irrit. 2	etching-/irritant effect on the skin	calculation method.
Eye Irrit. 2	Severe eye damage/irritation	calculation method.

Abbreviations and acronyms

ADR	European Convention on the International Carriage of Dangerous Goods by Road
AGW	Occupational exposure limit
BGW	Biological limit value
CAS	Chemical Abstracts Service
CLP	Classification, labelling and packaging
CMR	carcinogen, mutagenic and/or toxic to reproduction
DIN	German Institute for Standardization / Standard of the German Institute for Standardization
DNEL	Derived non-effect concentration
EAKV	Regulation establishing the European Waste Catalogue
EC	Effective concentration
EG	European Community
EN	European standard
IATA-DGR	Association for International Air Transport

Safety data sheet

in accordance with decree (EG) Nr. 1907/2006 (REACH)

in accordance with decree (EU) 2015/830



Article-No.: 1180 Scheidel Asur Allround Stripper
Printing date: 12.09.2019 Processing date:12.09.2019
Version: 4.0 Issue: 09.09.2019

DE

IBC-Code	International Code for the Construction and Equipment of Ships for the Carriage of Dangerous Chemicals as Bulk Goods
ICAO-TI	Technical instructions from the International Civil Aviation Organisation (ICAO) Regulations on the carriage of dangerous passengers by air
IMDG-Code	International Code for the Carriage of Dangerous Goods by Sea
ISO	International Organization for Standardization
LC	Lethal concentration
LD	Lethal dose
MAK	Maximum workplace concentration
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Estimated non-effect concentration
REACH	Registration, evaluation, authorisation and restriction of chemical substances
RID	Rules on the international transport of dangerous goods by rail
UN	United Nations
VOC	Volatile organic compounds
vPvB	very persistent and very bioaccumulative

For more information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information in this safety data sheet is in line with our current state of knowledge as well as national and EU regulations. The product may not be used without written permission, other than the purpose specified in Chapter 1. It is always the responsibility of the user to take all necessary measures to meet the requirements laid down in the local rules and laws. The information in this safety data sheet describes the safety requirements of our product and does not represent an assurance of product characteristics.