

Page 1/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.03.2020 Version number 6 Revision: 18.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Epoxy BS 3000 M Komp. A

Article number: 6370-79

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services,

craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC11a Widespread use of articles with low release (indoor)

Technical function Plating agent

Uses advised against No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Postfach 1255

D-49624 Löningen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985
Information department:

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010

E-Mail: sales@remmers.co.uk

1.4 Emergency telephone number:

during working hours:

U.K.: Tel.: +44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Remmers (UK) Limited

Unit B1 The Fleming Centre

West Sussex RH10 9NN

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

Printing date 18.03.2020 Version number 6 Revision: 18.03.2020

Trade name Epoxy BS 3000 M Komp. A

(Contd. of page 1)

Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

polyamine adduct

Hazard statements

H318 Causes serious eye damage.

Precautionary statements

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Additional information:

EUH208 Contains 2,4,7,9-Tetramethyl-5-decin-4,7-diol, ethoxyliert. May produce an allergic reaction. EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Resin mixture.

Dangerous components:		
CAS: 260549-92-6	polyamine adduct Eye Dam. 1, H318	≥20-<40%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17-XXXX	titanium dioxide Ĉarc. 2, H351	≥10-<20%
CAS: 9014-85-1 NLP: 500-022-5 Reg.nr.: 01-2119954393-33-XXXX	2,4,7,9-Tetramethyl-5-decin-4,7-diol, ethoxyliert Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-≤0.5%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

After inhalation Take affected persons into the open air and position comfortably

After skin contact If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

(Contd. on page 3)

Printing date 18.03.2020 Version number 6 Revision: 18.03.2020

Trade name Epoxy BS 3000 M Komp. A

(Contd. of page 2)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Water mist

Water spray jet

Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Carbon dioxide

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic substances cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: No special requirements.

Information on storage in a common storage facility: Store away from oxidising agents.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Com	Components with limit values that require monitoring at the workplace:		
CAS	CAS: 13463-67-7 titanium dioxide		
WEL	WEL Long-term value: 10* 4** mg/m³		
	*total inhalable **respirable		

Additional information: The lists that were valid during compilation were used as a basis.

Printing date 18.03.2020 Version number 6 Revision: 18.03.2020

Trade name Epoxy BS 3000 M Komp. A

(Contd. of page 3)

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Be sure to clean skin thoroughly before pauses and after work.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment: Not necessary if room is well-ventilated.

Protection of hands:

Impervious gloves

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Face protection

Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties **General Information** Appearance: Form: Fluid Colour: Different, according to dye Odour: Amine-like **Odour threshold:** Not determined. pH-value: Not determined. Change in condition Melting point/freezing point: Not determined Initial boiling point and boiling range: 100 °C Flash point: >100 °C Inflammability (solid, gaseous) Not applicable. **Ignition temperature:** not applicable

(Contd. on page 5)

Version number 6 Revision: 18.03.2020 Printing date 18.03.2020

Trade name Epoxy BS 3000 M Komp. A

(Contd. of page 4)

Decomposition temperature: Self-inflammability: Product is not self-igniting. Explosive properties: Product is not explosive. Explosive Limits: Lower: Not determined. Upper: Not determined.		
Explosive properties: Product is not explosive. Explosive Limits: Lower: Not determined.		
Explosive Limits: Lower: Not determined.		
Lower: Not determined.		
Upper: Not determined.		
• • • • • • • • • • • • • • • • • • • •		
Vapour pressure: Not determined.		
Density at 20 °C: 1.4 g/cm ³		
Relative density Not determined.		
Vapour density Not determined.		
Evaporation rate Not determined.		
Solubility in / Miscibility with		
Water: Fully miscible		
Distribution coefficient (n-octanol/water): Not determined.		
Viscosity:		
dynamic at 20 °C: 750 mPas		
kinematic: Not determined.		
Solvent separation test < 3 %		
Organic solvents: 0.2 %		
Water: 18.7 %		
Solid content: 68.0 %		
9.2 Other information No further relevant information available.		

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

- 10.3 Possibility of hazardous reactions Exothermic reaction with acids
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Acids

10.6 Hazardous decomposition products:

None if used properly. None if stored properly.

At high temperatures, the following may occur:

ammonia

Irritating gases/vapours Poisonous gases/vapours

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification: No further relevant information available.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eve damage/irritation:

Causes serious eve damage.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met. STOT-repeated exposure: Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 18.03.2020 Version number 6 Revision: 18.03.2020

Trade name Epoxy BS 3000 M Komp. A

(Contd. of page 5)

Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

32311311 11 ITanisport Information		
14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.		
Transport/Additional information:	Not a hazardous good according to the above regulations.	
UN "Model Regulation":	Void	
·	(O-11)	

(Contd. on page 7)

Printing date 18.03.2020 Version number 6 Revision: 18.03.2020

Trade name Epoxy BS 3000 M Komp. A

(Contd. of page 6)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations

Other regulations, limitations and prohibition ordinances

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment."

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Relevant phrases

H317 May cause an allergic skin reaction.

H318 Causes serious eve damage.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3