

iQ-Therm 50



Dimensions (length x breadth)	Availability		
	Quantity per pallet	8	8
	Packaging unit		
	Type of container	Package	Package
	Container code	14	08
	Art. no.		
[abmessungen0]	0241	■	
[abmessungen1]	0242		■
1200 mm x 600 mm, thickness 80 mm (± 2 mm)	0243		■

Range of use



- Mould control and prevention in existing buildings
- Implementation of the hygienic minimum heat insulation level in existing buildings
- Improving the room climate by increasing the wall surface temperature

Property profile

- [EG_SCH_29]
- Water vapour permeable
- Capillary-active
- [EG_SCH_27]
- Low construction height
- Easy to work
- [EG_SCH_28]

Certificates

- [Umwelt-Produktdeklaration](#)
- [Übereinstimmungszertifikat AbZ_ÜPGU](#)
- [Prüfbericht FIW, München](#)
- [Klassifizierung Brandverhaltens nach DIN EN 13501-1-MPA Braunschweig](#)
- [Prüfung Brandverhalten DIN EN ISO 11925-2-FIW München](#)
- [DIBt Allgemeine bauaufsichtliche Zulassung](#)
- [Untersuchungsbericht_Baustoffklasse DIN 4102-1_MPA Braunschweig](#)
- [Untersuchungsbericht_DIN EN ISO 11925-2_MPA Braunschweig](#)
- [Allgemeines bauaufsichtliches Prüfzeugnis - MPA Braunschweig](#)
- [Prüfzeugnis Brandverhalten 4102-1 incl. Oberputz iQ-Top SP - MPA Braunschweig](#)



- Prüfzeugnis Brandverhalten 4102-1 incl. Oberputz iQ-Top SLS - MPA Braunschweig
- Werterhaltungstipps Schimmel-Saniersysteme
- Informationen zur Ökobilanz, Baubiologie, Gesundheit und Emissionen
- Übereinstimmungszertifikat AbP_MPA-BS
- Erklärung zur HBCD-Freiheit (Flammschutzmittel)

Possible system products

- iQ Fix (0225)
- Tex 4/100 (3880)
- Tex 6.5/100 (0236)
- iQ-Top SLS (0230)
- iQ-Fill Q4 (0233)
- iQ-Paint (0237)

Preparation


■ Substrate requirements

The substrate must be clean and capable of bearing a load.
The substrate must be level.

■ Substrate preparation

Level off and even out highly uneven substrates – use SP Levell to seal joints and even out surfaces.

Directions



Pre-wet the substrate.

[VA1_iQ_9]

[VA1_iQ_10]

Position and press on the boards from the bottom up.
Align using a floating rule.

Tips on use

Mark the desired dimensions on the board.
Cut using a keyhole saw or hand-held circular saw.
Rework the cut edges with a rasp or file if necessary.
[VA2_SCH_10]
Avoid cross joints.

Notes

Deviations from applicable regulations must be agreed separately.

Storage / Shelf life

Dry and frost-free.



Disposal

The product must be disposed of in accordance with the official regulations.

Declaration of performance

- **Leistungserklärung**



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.