

PRODUCT DATA SHEET

HPC 203

CI/SfB

April 2008

SL1 - SHADOW LIFTER

DESCRIPTION: A specially formulated alkaline cleaner for the removal of stubborn graffiti shadow from brickwork, stone and concrete

ADVANTAGES: Will effectively remove unsightly shadows remaining after graffiti removal. Will also remove general soiling and staining from brickwork.

COLOUR: Amber coloured liquid.

PACK SIZE: Supplied in 5, 10 and 25 Litre drums.

COVERAGE RATE: Should be applied at 5m²/Litre.


PREPERATION: Areas to be cleaned should be wetted prior to application to prevent streaking.

APPLICATION: Apply undiluted SL1 with a bristle brush to the affected area starting at the bottom edge and working upwards.

STORAGE: Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE: 12 months (in original sealed container).

HEALTH & SAFETY: Refer to health and safety sheets.



Protective Coatings Ltd.

METHOD STATEMENT

FOR THE REMOVAL OF GRAFFITI SHADOW USING SL1

ITEM	DESCRIPTION	QUANTITY	UNIT	RATE	COST
1	Pressure wash the area to be treated to prevent any unnecessary absorption and streaking.				
2	Apply undiluted SL1 with a bristle brush to the affected area at a coverage rate of 5m ² /Litre starting at the bottom edge working upwards.				
3	Allow to dwell for 1-2 minutes before rinsing.				
4	Pressure wash with a pump capable of 1500 psi @ 14 rpm with a slow even movement keeping the lance 15-20 cm away from the surface until complete rinsing has been achieved				
		CARRIED TO COLLECTION			