

Product Data Sheet



CONTEC USP-705 RUST REMOVER



PRODUCT DESCRIPTION

Contec USP-705 Rust Remover is a concentrated detergent/acid pre-treatment for the removal of rust and metal oxide deposits from deteriorated surfaces.

Contec USP-705 Rust Remover is ideally suited for the daily cleaning of tiled, porcelain stoneware, granite worktops and marble surfaces.

Contec USP-705 Rust Remover is an aqueous-based treatment used to prepare stone and concrete surfaces before application of a finishing product.

ADVANTAGES

A powerful surface treatment that outperforms standard products, concentrated, odourless, with no need to rinse. Fast-acting, powerful degreasing and etching properties.

Water-based, non-hazardous, environmentally friendly and bio-degradable

Highly versatile: effective against all types of rust and metal oxide deposits and will remove grout blooms. Ready & easy to use, no need to pH neutralize after rinsing and does not alter the aesthetic of the treated surface.

PACKAGING

1, 5, & 25 ltr Units

TECHNICAL DATA


Physical State at 20 °C: Liquid Appearance: Colourless Odour: Characteristic

pH: Acidic

Solubility in water: Fully soluble **Flash Point [°C]**: Not applicable



Product Data Sheet



APPLICATION

Always test apply on a small hidden portion of the substrate before commencing works.

This product is specially designed to remove rust, metal oxide deposits and clean all synthetic and stone surfaces. Shake the container well before use

To apply:

Use: Sponge or cloth and then leave it to soak, allowing 5-30 minutes to act. When immersing items, allow to soak for 20 minutes, take out the parts, brush and rinse in running water

Guidelines for use:

Apply product to the surface using a sponge, moving from bottom to top, agitate with a firm bristle brush then wipe with a cloth or soft wipe. No rinsing required. The surface is ready to be treated or painted as soon as it has been wiped down and allowed to dry.

STORAGE/CLEANING

Keep in a dry place (between 5°C and 30°C).

Storage: 24 months following the production date when kept in the original unopened container. Immediately after you have finished clean all tools and equipment with water.

RECOMMENDATIONS

Contec USP-705 Rust Remover contains is a corrosive product, and it is advised to wear gloves, safety goggles and an adequate combination during the period of use

To obtain the best look and results on application, **Contec USP-705 Rust Remover** should be shaken before use and must be used only when the temperature of the surfaces to be treated is > 5°C

Do not apply during rainy or very hot weather.

HEALTH & SAFETY

<u>Respiratory Protection</u>: Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed.

Hand Protection: Wear domestic gloves.

Skin Protection: Wear protective clothing over exposed areas of skin.

Eye Protection: Wear safety goggles.

If swallowed: Do not induce vomiting. Contact a doctor or a specialist.

KEEP OUT OF THE REACH OF CHILDREN

TECHNICAL SUPPORT

Conservation Technology

Davitt Road, Dublin 12 Tel: + 353 1 455 9511

E-mail: info@conservationtech.ie

Important: The content of this documentation is based on our experience of the product. Conservation Technology guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with Conservation Technology's products or bad weather conditions. For further information, refer to the safety data sheet.

Date of last update: 02/09/2020

Conservation Technology Davitt Road Dublin 12 Ph: +353 1 455 9511 E: info@conservationtech.ie W: www.conservationtech.ie