

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 01.01.2021

Version number 13

Revision: 01.01.2021

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name** **HK-LASUR / HK Stain****Article number:** 2250-94**1.2 Relevant identified uses of the substance or mixture and uses advised against**  
**Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category** PC9a Coatings and paints, thinners, paint removers**Process category**

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

**Environmental release category**

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

ERC10a Widespread use of articles with low release (outdoor)

**Application of the substance / the mixture** Coating**Uses advised against** No further relevant information available.**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Remmers GmbH

Bernhard-Remmers-Str. 13

D-49624 Lönigen / Germany

9QU

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

**Information department:**

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010

E-Mail: sales@remmers.co.uk

Remmers (UK) Limited

Unit 4 , Lloyds Court

Manor Royal, Crawley – West Sussex RH10

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

**1.4 Emergency telephone number:**

during working hours:

+44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

National Poisons Information Service (NPIS):

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.01.2021

Version number 13

Revision: 01.01.2021

Trade name **HK-LASUR / HK Stain**

(Contd. of page 1)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS08

Signal word Danger

#### Hazard-determining components of labelling:

Alkanes, C10-13

hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics

#### Hazard statements

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

#### Dangerous components [% w/w]:

EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39-XXXX	Alkanes, C10-13 Asp. Tox. 1, H304, EUH066	≥40-<60%
EC number: 920-360-0 Reg.nr.: 01-2119448343-41-XXXX	hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics Asp. Tox. 1, H304	≥20-<40%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17-XXXX	titanium dioxide Carc. 2, H351	≥5-<10%

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.01.2021

Version number 13

Revision: 01.01.2021

Trade name **HK-LASUR / HK Stain**

(Contd. of page 2)

CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7	3-iodo-2-propynyl butylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.25-<1%
--	--	-----------

**Additional information**

Benzene content: < 0,1% Note P is applicable. It is not necessary to classify nor to mark the product as carcinogenic.

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures****After inhalation**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness bring patient into stable side position for transport.

**After skin contact**

Wash immediately with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact** Rinse opened eye for several minutes under running water.

**After swallowing** Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

**4.3 Indication of any immediate medical attention and special treatment needed**

To avoid dermatitis (skin inflammation), use skin cream.

symptomatic treatment

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents**

Foam

Water spray jet

Water mist

**5.2 Special hazards arising from the substance or mixture**

May be released in case of fire

Carbon monoxide (CO)

Carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

**5.3 Advice for firefighters****Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

**Additional information**

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources

Ensure adequate ventilation

**6.2 Environmental precautions:**

Do not allow to enter the ground/soil.

Prevent from spreading (e.g. by confining or oil barrier).

This product may not be allowed to reach surface water because it is toxic to aquatic environments.

Inform responsible authorities in case product reaches bodies of water or sewage system.

**6.3 Methods and material for containment and cleaning up:**

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 01.01.2021

Version number 13

Revision: 01.01.2021

Trade name **HK-LASUR / HK Stain**

(Contd. of page 3)

Dispose of contaminated material as waste according to item 13.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling** Use only in well ventilated areas.**Information about protection against explosions and fires:**

Fumes can combine with air to form an explosive mixture.

**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and containers:** No special requirements.**Information on storage in a common storage facility:** Store away from food.**Further information about storage conditions:**

Store container in a well ventilated position.

Protect from frost.

**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:****CAS: 136-52-7 cobalt(II) 2-ethylhexanoate**

WEL	Long-term value: 0.1 mg/m <sup>3</sup> as Co; Carc, Sen
-----	--

**Additional information:** The lists that were valid during compilation were used as a basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see item 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.

Apply solvent-resistant skin protection preparation before beginning work.

Keep away from food, beverages and animal feed.

Wash hands before pauses and after work.

**Respiratory equipment:** Filter A/P2.**Hand protection**

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Safety glasses recommended during refilling.**Body protection:** Protective work clothing.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.01.2021

Version number 13

Revision: 01.01.2021

Trade name **HK-LASUR / HK Stain**

(Contd. of page 4)

## \* SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

Colour:	Different, according to dye
Odour:	Solvent-like
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	Not determined
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
Flash point:	> 60 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	16 +/-2 s (DIN 53211/4)
dynamic:	Not determined.
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.85±0.03 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.

### 9.2 Other information

Appearance:	
Form:	Liquid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	not applicable
Explosive properties:	Product is not explosive.
Solvent separation test	< 3 %
VOC EU	< 400 g/l
Change in condition	
Evaporation rate	Not determined.

#### Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.01.2021

Version number 13

Revision: 01.01.2021

Trade name **HK-LASUR / HK Stain**

(Contd. of page 5)

**Desensitised explosives**

Void

**SECTION 10: Stability and reactivity****10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if handled and stored according to specifications.

**10.3 Possibility of hazardous reactions**

Used empty containers may contain product gases which form explosive mixtures with air

**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity:** Based on available data, the classification criteria are not met.**LD/LC50 values that are relevant for classification:****Alkanes, C10-13**

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)

**Skin corrosion/irritation:** Based on available data, the classification criteria are not met.**Serious eye damage/irritation:** Based on available data, the classification criteria are not met.**Sensitisation:** Based on available data, the classification criteria are not met.**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.**Carcinogenicity:** Based on available data, the classification criteria are not met.**Reproductive toxicity:** Based on available data, the classification criteria are not met.**STOT-single exposure:** Based on available data, the classification criteria are not met.**STOT-repeated exposure:** Based on available data, the classification criteria are not met.**Aspiration hazard:**

May be fatal if swallowed and enters airways.

**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

**\* SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects****Remark:** Harmful to fish**Additional ecological information:****General notes:**

Do not allow product to reach ground water, bodies of water or sewage system, even in small quantities.

Hazardous to drinking water even if extremely small quantities leak into soil.

Harmful to aquatic organisms

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.01.2021

Version number 13

Revision: 01.01.2021

Trade name **HK-LASUR / HK Stain**

(Contd. of page 6)

## SECTION 13: Disposal considerations

**Recommendation**

Liquid material remains are to be disposed of at collection facilities for old varnishes.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

**European waste catalogue**

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

**Uncleaned packaging:****Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

## SECTION 14: Transport information

**14.1 UN number or ID number**

ADR, ADN, IMDG, IATA Void

**14.2 UN proper shipping name**

ADR, ADN, IMDG, IATA Void

**14.3 Transport hazard class(es)**ADR, ADN, IMDG, IATA  
Class Void**14.4 Packing group**

ADR, IMDG, IATA Void

**14.5 Environmental hazards:**

Marine pollutant: No

**14.6 Special precautions for user**

Not applicable.

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

**Transport/Additional information:**

Not a hazardous good according to the above regulations.

**UN "Model Regulation":**

Void

## \* SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

**Relevant phrases**

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 01.01.2021

Version number 13

Revision: 01.01.2021

**Trade name HK-LASUR / HK Stain**

(Contd. of page 7)

- H331 Toxic if inhaled.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

**Classification according to Regulation (EC) No 1272/2008** Calculation method**Department issuing data specification sheet:** Product Safety department / EHS**Version number of previous version:** 12**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral – Category 4

Acute Tox. 3: Acute toxicity - inhalation – Category 3

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3