



Contec AG

THE ONE COAT WATER WASHABLE ANTI GRAFFITI COATING

Availability

Pallet:	-
Size:	5L
Range:	Clear Gloss, Clear Semi Matt, RAL Colour

Advantages

- One coat application
- Graffiti will not adhere to the surface
- Once dry, graffiti can be removed quick and easy by using warm soapy water
- No re-application required
- Most surfaces can be protected with just one coat
- Approx Coverage rate - One coat @ 8 m² / Litre
- WFT – 125 microns, DFT – 95 microns
- Touch dry in 1-2 hours, fully cured in 6 hours

Description

Contec AG Clear Coating is a specially formulated single pack external coating designed to give effective protection against both fly-posting and graffiti. RAL Colours also available.

Preparation

Ensure surfaces to be treated are clean, free from contamination and dry. To prevent concrete surfaces darkening and application to very porous surfaces, it is advisable to apply one coat of Contec WB Concrete Sealer.

Application

- By brush/roller or spray.
- Apply in one heavy coat. (Do not apply too thin)
- Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.

Graffiti Removal

Graffiti should be removed using warm soapy water. If using a pressure washer, no more than 70bar should be used.

Equipment Care

All equipment should be cleaned with white spirit.

Storage

Store away from direct sunlight and sources of heat. Protect from frost. Do not allow moisture into the can.

Shelf life

12 months (in original sealed container)

Technical Data Sheet

Contec



Technical information

Volume Solids (Clear):	75%
Volume Solids (Colour):	70%
Coverage Rate (Clear):	One coat @ 8 m ² / Litre WFT – 125 microns DFT – 95 microns
Coverage Rate (Colour):	One coat @ 8-10 m ² / Litre WFT – 125 microns DFT – 90 microns
Drying Time:	Touch Dry :.....1-2 Hours Full Cure :.....6 Hours

The information and recommendations given in this technical data sheet reflect our current knowledge, laboratory tests and experience. For this reason, our guarantee is limited to the quality of the product supplied. This company shall not assume any liability arising from misuse of our products.

Contact

Conservation Technology
Neolith House,
Davitt Road,
Dublin 12, Ireland

TEL: +353 (1) 455 9511
EMAIL: info@conservationtech.ie
WEB: www.conservationtech.ie