

The RITE SOLUTION

STANDARD NON-CAUSTIC T.F.R.

TECHNICAL INFORMATION SHEET

IMPORTANT NOTE:

This information sheet is intended to provide a general overview of Standard Non-Caustic T.F.R. and its potential uses. For further technical and safety information and before attempting usage, please refer to the Standard Non-Caustic T.F.R. MSDS

DESCRIPTION

Standard Non-Caustic T.F.R. is a non-caustic alkaline cleaner designed for the use of routine cleaning of all types of decorative paintwork.

PACK SIZES

5 Litres
10 Litres
25 Litres
210 Litres
1000 Litres

USES

Standard Non-Caustic T.F.R. is designed to clean and remove traffic film from all types of vehicle exteriors without damaging paintwork. It can also be used for the removal of light oil from industrial machinery.

DIRECTIONS

Standard Non-Caustic T.F.R. is best applied using hot or cold high pressure cleaning equipment. Depending on the level of soiling, adjust the dilution to between 1% and 2%. Rinse thoroughly with clean water after application.

SUPPLIED BY: Neolith Ltd, Davitt Road, Dublin 12 Tel:
353-1-4559511

The information contained in this publication is to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information or in respect of any recommendations or suggestions which may be made or that any use will not infringe any patent