



# Add 250

## Polymer granules

Availability	
Quantity per pallet	480
Packaging unit	0,25 kg
Type of container	Can
Container code	83
Art. no.	
6271	■

**Application rate** Up to 0.05 kg on 1 kg of binder

**Range of use** ■ Polymer granules for producing slip-resistant sealants

**Property profile** ■ Colour-neutral  
 ■ Easy to mix in

Characteristic data of the product	Grain density	1.1 g/cm <sup>3</sup>
	Particle size	approx. 0.25 mm

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

**Certificates** > [High pressure/superheated steam cleanability system test](#)  
 > [Slip-resistant coatings system test A](#)

**Possible system products** > [Epoxy BS 2000 \(6001\)](#)  
 > [Epoxy BS 3000 M \(6370\)](#)  
 > [Epoxy BS 3000 SG \(6380\)](#)


**Production of the mixture**

Add the granules to the mixed sealant.  
 Mix thoroughly with a slow-speed electric mixer (approx. 300 - 400 rpm).  
 Insufficient mixing is indicated by streaks forming.

**Directions** For professional users only!

Apply the mixed material according to the instructions given for the sealant.



<b>Notes</b>	The granules are only suitable for individual layers < 200 µm thick. Further notes on working, system construction and maintenance of the listed products can be found in the latest Technical Data Sheets and the Remmers system recommendations.
<b>Storage / Shelf life</b>	Unlimited if stored dry.
	
<b>Safety data / Regulations</b>	For professional users only! Further information concerning safety during transport, storage and handling as well as on disposal and ecology can be found in the latest Safety Data Sheet.
<b>Personal protective equipment</b>	This information can be obtained from the current Safety Data Sheets and/or the relevant professional associations.
<b>Disposal</b>	Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.