

Page 1/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.10.2021 Version number 5 Revision: 24.10.2017

#### \* SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Trade name SL Fill Q2 (Mould Restoration Filler)

Article number: 2996

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Sector of Use** 

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services,

craftsmen)

Product category PC9b Fillers, putties, plasters, modelling clay

**Process category** 

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

**Environmental release category** 

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC11a Widespread use of articles with low release (indoor)

Application of the substance / the mixture Anti-moisture agent

Uses advised against No further relevant information available.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Bernhard-Remmers-Str. 13

D-49624 Löningen / Germany

Manor Royal, Crawley - West Sussex RH10 9QU

Tel.: +49(0)5432/83-0 fon +44 (0) 1

fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

Remmers (UK) Limited

Unit 4, Lloyds Court

Fax: +49(0)5432/3985

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

#### 1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

#### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT RE 2 H373 May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

(Contd. on page 2)

Printing date 11.10.2021 Version number 5 Revision: 24.10.2017

## Trade name SL Fill Q2 (Mould Restoration Filler)

(Contd. of page 1)

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms





GHS05 GHS08

#### Signal word Danger

#### Hazard-determining components of labelling:

cement

quartz flour

calcium hydroxide

#### **Hazard statements**

H315 Causes skin irritation.

H318 Causes serious eye damage.

H373 May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P260 Do not breathe dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 Other hazards low chromate content according to directive 2003/53 EG

#### Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

**Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 65997-15-1 EINECS: 266-043-4	cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	10-20%
CAS: 1305-62-0 EINECS: 215-137-3 Reg.nr.: 01-2119475151-45- XXXX	calcium hydroxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	5-10%
CAS: 14808-60-7 EINECS: 238-878-4 Reg.nr.: 01-2120770509-45- XXXX	quartz flour STOT RE 1, H372	1-2.5%

#### **Additional information**

The preparation has a low chromate content according to directive 2003/53/EG.

For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**After inhalation** Seek medical treatment in case of complaints.

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021 Version number 5 Revision: 24.10.2017

## Trade name SL Fill Q2 (Mould Restoration Filler)

(Contd. of page 2)

#### After skin contact

If skin irritation continues, consult a doctor.

Wash immediately with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing Call a doctor immediately.

Information for doctor see item 3

#### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing agents No special measures required.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

#### 5.3 Advice for firefighters

**Protective equipment:** No special measures required.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid causing dust.

Avoid skin contact. Avoid eye contact.

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

#### 6.2 Environmental precautions:

Avoid uncontrolled admittance of water. Avoid uncontrolled runoff after admittance of water. Avoid runoff into sewage system and receiving water.

#### 6.3 Methods and material for containment and cleaning up:

Keep away from water.

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### 6.4 Reference to other sections

Hardens after contact with water. After hardening it can be disposed of as concrete (European waste catalogue: EWC-Code: 170101).

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Protect against moisture. Keep out of reach of children. Avoid skin contact. Avoid eye contact.

Thorough removal of dust.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of dust.

#### Information about protection against explosions and fires:

Keep breathing equipment ready.

No special requirements.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### **Storage**

Requirements to be met by storerooms and containers: No special requirements.

Information on storage in a common storage facility: none

#### Further information about storage conditions:

Store dry.

Protect from humidity and keep away from water.

Keep container tightly closed.

#### 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

Printing date 11.10.2021 Version number 5 Revision: 24.10.2017

## Trade name SL Fill Q2 (Mould Restoration Filler)

(Contd. of page 3)

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Components with limit values that require monitoring at the workplace:		
CAS: 65997-15-1 cement		
WEL	Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust	
CAS:	CAS: 1305-62-0 calcium hydroxide	
WEL Long-term value: 5 mg/m³		

Additional information: The lists that were valid during compilation were used as a basis.

#### 8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

## Individual protection measures, such as personal protective equipment

## General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Observe Professional Association regulations.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Store protective clothing separately.

Avoid contact with eyes and skin.

#### Respiratory equipment:

Short term filter device:

Particle-Filter P2

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

#### Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### **Eye/face protection**

Avoid contact with eyes. In case of eye contact, rinse immediately and thoroughly with water. Seek medical advice.

Tightly sealed safety glasses.

**Body protection:** Protective work clothing.

#### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

**General Information** 

Colour:WhitishOdour:OdourlessOdour threshold:Not determined.Melting point/freezing point:> 1000 °C

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.10.2021 Version number 5 Revision: 24.10.2017

## Trade name SL Fill Q2 (Mould Restoration Filler)

(Contd. of page 4)

Boiling point or initial boiling point and boiling

range Not determined Flammability Not determined.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicableDecomposition temperature:Not determined.

pH (10 g/l) at 20 °C ca. 12

Viscosity:

**Kinematic viscosity dynamic:**Not applicable.
Not applicable.

Solubility

Water: Soluble

**Partition coefficient n-octanol/water (log value)** Not determined. **Vapour pressure:** Not applicable.

Density and/or relative density

Density:Not determinedRelative densityNot determined.Bulk apparent density at 20 °C1.2 kg/dm3Vapour densityNot applicable.Particle characteristicsSee item 3.

9.2 Other information

Appearance:

Form: Powder

Important information on protection of health

and environment, and on safety.

**Ignition temperature:** not applicable

**Explosive properties:** Product is not explosive.

**VOC EU** 

Solid content: 100.0 %

Change in condition

**Evaporation rate** Not applicable.

Information with regard to physical hazard

classes **Explosives** Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Oxidising solids Void Organic peroxides Void **Corrosive to metals** Void

#### **SECTION 10: Stability and reactivity**

**Desensitised explosives** 

Void

Printing date 11.10.2021 Version number 5 Revision: 24.10.2017

## Trade name SL Fill Q2 (Mould Restoration Filler)

(Contd. of page 5)

#### 10.2 Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

Avoid the entrance of moisture

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

#### LD/LC50 values that are relevant for classification:

#### CAS: 1305-62-0 calcium hydroxide

Oral LD50 7340 mg/kg (rat)

Skin corrosion/irritation: Light irritating effect possible.

#### Serious eye damage/irritation: Causes serious eye damage.

**Sensitisation:** Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

**Carcinogenicity:** Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met. **STOT-single exposure:** Based on available data, the classification criteria are not met.

STOT-repeated exposure:

May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Aspiration hazard: Based on available data, the classification criteria are not met.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

#### 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

#### 12.7 Other adverse effects

#### Additional ecological information:

#### General notes:

Do not allow undiluted or non-neutralised product to reach the sewage system or receiving waters.

Do not allow product to reach ground water, bodies of water or sewage system.

### **SECTION 13: Disposal considerations**

#### Recommendation

May be used again if taken up in dry. After the addition of water and subsequent hardening, dispose of as concrete.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

### European waste catalogue

17 01 01 concrete

(Contd. on page 7)

Printing date 11.10.2021 Version number 5 Revision: 24.10.2017

## Trade name SL Fill Q2 (Mould Restoration Filler)

(Contd. of page 6)

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations. **Recommended cleaning agent:** Water, if necessary with cleaning agent.

#### **SECTION 14: Transport information**

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments Not applicable.	
Transport/Additional information:	Not a hazardous good according to the above regulations.
UN "Model Regulation":	Void

### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

**National regulations** 

Other regulations, limitations and prohibition ordinances

Professional Association Principles/Industrial Medicine regulations, e.g. principles of industrial medicine Occupational Safety Regulations.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

### Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

#### Department issuing data specification sheet: Product Safety department / EHS

#### Version number of previous version: 4

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

(Contd. on page 8)

Page 8/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.10.2021 Version number 5 Revision: 24.10.2017

## Trade name SL Fill Q2 (Mould Restoration Filler)

(Contd. of page 7)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2