

Remmers (UK) Limited

West Sussex RH10 9NN

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

Unit B1 The Fleming Centre

Page 1/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.04.2020 Version number 5 Revision: 09.04.2020

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

# Trade name Color SH (Silicate Paint D)

**Article number: 0630, 0634** 

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Priming

Uses advised against No further relevant information available.

## 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Postfach 1255 D-49624 Löningen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985 Information department:

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010

E-Mail: sales@remmers.co.uk

#### 1.4 Emergency telephone number:

during working hours:

U.K.: Tel.: +44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

### Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist

### 2.3 Other hazards

Results of PBT and vPvB assessment

**PBT:** Not applicable.

(Contd. on page 2)

Printing date 09.04.2020 Version number 5 Revision: 09.04.2020

# Trade name Color SH (Silicate Paint D)

(Contd. of page 1)

vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of the substances listed below with harmless additions.

Dangerous components:		
CAS: 13463-67-7	titanium dioxide	≥5-<10%
EINECS: 236-675-5	Carc. 2, H351	
Index number: 022-006-00-2		
Reg.nr.: 01-2119489379-17-XXXX		
CAS: 1312-76-1	Silicic acid, potassium salt	≥1-<2.5%
Reg.nr.: 01-2119456888-17-XXXX	Skin Irrit. 2, H315; Eye Irrit. 2, H319	
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,	≥1-<2.5%
Reg.nr.: 01-2119463258-33-XXXX		
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	

Additional information For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General information No special measures required.

After inhalation No special requirements.

After skin contact If skin irritation continues, consult a doctor.

After eye contact Call a doctor immediately.

After swallowing Rinse out mouth and then drink plenty of water.

# 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

Danger Long-term or repeated exposure may cause inflammation of the skin (dermatitis).

## 4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

#### Suitable extinguishing agents

CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

#### 5.3 Advice for firefighters

Protective equipment: No special measures required.

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

Ensure adequate ventilation

### 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Dilute with plenty of water.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

# 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

(Contd. on page 3)

Printing date 09.04.2020 Version number 5 Revision: 09.04.2020

# Trade name Color SH (Silicate Paint D)

(Contd. of page 2)

## **SECTION 7: Handling and storage**

7.1 Precautions for safe handling No special precautions necessary if used correctly.

#### 7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: Store in alkali resistant containers.

Information on storage in a common storage facility: none

Further information about storage conditions: Protect from frost.

7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

### 8.1 Control parameters

# Components with limit values that require monitoring at the workplace:

CAS: 13463-67-7 titanium dioxide

WEL Long-term value: 10\* 4\*\* mg/m³ \*total inhalable \*\*respirable

Additional information: The lists that were valid during compilation were used as a basis.

#### 8.2 Exposure controls

#### Personal protective equipment

## General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Wash hands before pauses and after work.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

# Respiratory equipment:

In case of insufficient ventilation/or spraying procedures: Respiratory equipment with particle filter P 2

## Protection of hands:

Impervious gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

# Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** if there is a risk of splashes **Body protection:** Protective work clothing.

(Contd. on page 4)

Printing date 09.04.2020 Version number 5 Revision: 09.04.2020

# Trade name Color SH (Silicate Paint D)

(Contd. of page 3)

SECTION 9: Physical and chemical propertie	S
--	---

SECTION 9: Physical and chemical p	properties	
9.1 Information on basic physical and chemical properties		
General Information		
Appearance:		
Form:	Fluid	
Colour:	According to product specification	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value at 20 °C:	<11.5	
Change in condition		
Melting point/freezing point:	Not determined	
Initial boiling point and boiling range:	> 100 °C	
Flash point:	Not applicable	
Inflammability (solid, gaseous)	Not applicable.	
Ignition temperature:	not applicable	
Decomposition temperature:	Not determined.	
Self-inflammability:	Product is not self-igniting.	
Explosive properties:	Product is not explosive.	
Explosive Limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure at 20 °C:	23 hPa	
Density at 20 °C:	1.4 g/cm <sup>3</sup>	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	miscible	
Distribution coefficient (n-octanol/water)	: Not determined.	
Viscosity:		
dynamic at 20 °C:	2500 mPas	
kinematic:	Not determined.	
Solvent separation test	< 3 %	
VOC EU	<40 g/l	
9.2 Other information	No further relevant information available.	

# **SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability

# Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

- 10.3 Possibility of hazardous reactions Exothermic reaction with acids
- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: Acids
- 10.6 Hazardous decomposition products:

None if used properly.

Printing date 09.04.2020 Version number 5 Revision: 09.04.2020

# Trade name Color SH (Silicate Paint D)

(Contd. of page 4)

None if stored properly.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification: No further relevant information available.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: May cause irritation.

Sensitisation: Based on available data, the classification criteria are not met.

**Experience with humans:** 

Frequent or longer lasting skin contact may degrease and dry out skin which may lead to skin irritation and

inflammation (dermatitis).

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met. **STOT-single exposure:** Based on available data, the classification criteria are not met. **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

# Additional ecological information:

#### General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

#### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

## Recommendation

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions. Hardened material can be disposed of as building rubble.

# European waste catalogue

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

#### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations. **Recommended cleaning agent:** Water, if necessary with cleaning agent.

#### **SECTION 14: Transport information**

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

(Contd. on page 6)

Printing date 09.04.2020 Version number 5 Revision: 09.04.2020

# Trade name Color SH (Silicate Paint D)

(Contd. of page 5)

	( 1-3
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.	
Transport/Additional information:	Not a hazardous good according to the above regulations.
UN "Model Regulation":	Void

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

**National regulations** 

#### Other regulations, limitations and prohibition ordinances

Observe the usual protective measures when working and for storage.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

Classification according to Regulation (EC) No 1272/2008 Calculation method

# Department issuing data specification sheet: Product Safety department / EHS

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Page 7/7

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.04.2020 Version number 5 Revision: 09.04.2020

# Trade name Color SH (Silicate Paint D)

(Contd. of page 6)

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1