



Contec USP 200

EXTRA HIGH WATER AND STAIN REPELLENT IMPREGNATOR

Availability

Pallet: -
Size: 5L, 25L, 200L, 1000L
Colour: Clear

Advantages

- One coat application
- Stain and dirt resistant
- Non-stick and allows easy chewing gum removal
- No re-application required
- Reduces penetration of oil and water, frost damage and organic growth
- Approx Coverage rate - One coat @ 8 – 15 m² / Litre
- Highly resistant to weathering and UV exposure
- Moisture vapour permeable.
- Non-glossy appearance

Description

Contec USP 200 is a unique hydrophobic oil and water repellent treatment. Due to its excellent water repellent qualities, reduces penetration of oil and water, frost damage and organic growth. Stain and dirt resistant.

Preparation

Ensure surfaces to be treated are clean, free from contamination and dry. Treat all areas affected by organic growth with Remmers BFA.

Application

- Application by low pressure spray or by brush/roller, ensuring to avoid any sagging.
- On vertical surfaces, apply to full saturation starting from the bottom and working upwards.
- Typically, only one application is necessary, but porous substrates may require a second application.
- Apply the second application immediately after the first, ensuring the first doesn't dry out.
- Avoid application at temperatures below 5°C.
- Shake container well before use.

Uses

For use on brickwork, concrete, natural stone, reconstructed stone and blockwork. May also be used on wood.

Equipment Care

All equipment should be cleaned with water immediately after use.

Storage

Store away from direct sunlight and sources of heat. Protect from frost.

Technical Data Sheet

Contec



Shelf life

12 months (in original sealed container)

Technical information	
Coverage Rate	<ul style="list-style-type: none">• Granite 15 m² / Litre• Marble 13 m² / Litre• Terrazzo 8 m² / Litre• Engineering brick 8 m² / Litre• Polished concrete 8 m² / Litre• GRC 8 m² / Litre

The information and recommendations given in this technical data sheet reflect our current knowledge, laboratory tests and experience. For this reason, our guarantee is limited to the quality of the product supplied. This company shall not assume any liability arising from misuse of our products.

Contact

Conservation Technology
Neolith House,
Davitt Road,
Dublin 12, Ireland

TEL: +353 (1) 455 9511
EMAIL: info@conservationtech.ie
WEB: www.conservationtech.ie