

The RITE SOLUTION

TILT CLEANER

TECHNICAL INFORMATION SHEET

IMPORTANT NOTE:

This information sheet is intended to provide a general overview of Tilt Cleaner and its potential uses. For further technical and safety information and before attempting usage, please refer to the Tilt Cleaner MSDS

DESCRIPTION

Tilt Cleaner is a fast acting versatile cleaner developed for the road transport industry as a heavy soil and traffic film remover, for those jobs where the use of a strong alkaline detergent is required.

PACK SIZES

5 Litres
25 Litres
210 Litres

USES

Tilt Cleaner is very effective when used for routine cleaning of road transport tankers, box containers, curtain sided vehicles, tilt side trailers, cranes, diggers, tractors etc.

Tilt Cleaner also produces good results when used as a chassis cleaner for pre MOT cleaning

DIRECTIONS

Tilt Cleaner should be applied via hot or cold pressure washing equipment. Spray Tilt Cleaner on the vehicle surface at low pressure at a dilution of between 0.5% and 1% depending on the degree of soiling. A contact time of up to two minutes should be allowed for the detergent to penetrate before rinsing off with clean high pressure water.

To avoid damage to sign writing, dilute Tilt Cleaner 50:50 with water before use. Test any delicate metals before spraying.

On no account allow Tilt Cleaner to dry on the vehicle surface as this may result in staining.

SUPPLIED BY: Neolith Ltd, Davitt Road, Dublin 12
Tel: 353-1-4559511

The information contained in this publication is to the best of our knowledge, true and accurate, but since the conditions of use are beyond our control, no warranty is given or to be implied in respect of such information or in respect of any recommendations or suggestions which may be made or that any use will not infringe any patent